

Fisher Community Fair
2026 70s and newer Limited Weld RULES
Greg McCoy 217-714-9997

This class is open to all men and women 16 and over. 16 and 17 year old must have a signature by parent/guardian.

Each car/driver WILL ENTER FREE.

PARTICIPANT REGULATIONS

Driver may move forward or backward. Driver must make contact every 60 seconds or be disqualified. No sandbagging. If you sandbag the race will be stopped and the driver given a warning.. No team driving allowed, not even on a sandbagger. Cars must move when hit or show visible damage. No driver's door hits allowed.

PREPARATION OF CARS

This class will be limited to any year cars. No screws allowed. NO PLASTIC GAS TANKS (heavy duty plastic racing fuel cells are allowed). No wedging, no sedagons, no jeeps, no trucks (ranchero and el Caminos are considered trucks), no carryalls, no Hearst, no limos, no convertibles. No 1973 or older sub or full frame imperials. No 1970 or older suicide lincolns, 2 door or T-Birds. All glass, chrome, pot metal, lights, carpet, headliner, back seats, fiberglass and anything else that is flammable must be removed before reaching the exhibit area (do not break glass down in the doors). Trunks must be empty of all debris, spare tire rims, parts, etc. Wagons must have spare tire flap removed or a hole cut in it for inspectors to see. ABSOLUTELY NO welding besides what is stated in these rules. UNLIMITED 9-WIRE. 9 wire may go to the cage or halo bar. May use 1/4" cable with turnbuckle instead of 9 wire. You must have a number on both front doors big enough to read and bright enough color to see. Also must have a number on the roof sign. Use your choice of number. No profanity allowed on cars.

SAFETY RULES AND REGULATIONS

1. Cars must have at least one bar no more than 2. No bigger than 2 inches wide by 1/4" thick or 3/8 chain or 9 wire attached from roof down to dash area to prevent hood from coming in. No more than 4" on the roof and 4" on the dash. May be bolted or welded. Rear window bars are not allowed. 2. Radiator overflow hoses must be pointed at the ground and fastened so they cannot shoot water towards officials or other drivers. 3. Header pipes must be pointing straight up and cannot be aimed towards the front of cars. 4. If you have a hole in the fire wall it should be covered. 5. Safety belts required. 6. D.O.T. approved helmets mandatory. Any driver using an open face helmet will not be covered by insurance if facial injury occurs. 7. Safety glasses or shield recommended. 8. Mandatory-you must wear long pants and a shirt (fire suit recommended). 9. 2 fires and you are out unless it's a fuel fire then it's just 1 fire and you are out. 10. No alcoholic beverages or drugs allowed in the pit area or on the track. 11. NO PIT PERSONS ALLOWED ON THE TRACK. 12. Management does have the right to disqualify a car/driver at any time. Any person on track or causing trouble and not complying with the rules will be asked to leave (we can have you escorted off or have you arrested and you can be banned from running or being in the pit area at any future Demos). 13. Protests must be made no later than 5 minutes after the heat in question. No protests will be taken after the feature event. Only drivers are allowed to protest a car.

ENGINE

May use any engine and transmission. You may use a lower engine cradle with front head plate only for the sole purpose of protecting the engine block. No mid plates allowed. Must only come in contact with motor mounts. The motor mounts are the only thing that can touch the frame. 03 and newer must keep the factory aluminum engine cradle. 03 and new lower engine cradle can only bolt to the 4 bolt holes in the aluminum cradle, not the 4 bolts on the frame. May use a Grey Area style cradle and use 1/2" bolts and 1/2" SAE washers to bolt cradle to aluminum cradle. The cradle must not touch the frame in any way. No DP's. My have a pulley protector.or sway bar but not both.. You may use 2 chains to retain engine one on each side. No more than two links can be welded to frame. 03 and new engine chain must go to the lower cradle only. You will be allowed a plate under your motor mount to space your engine up if necessary. 1/2"